

ELEVAH® 70

The Elevah 70 is the aerial platform equipped with a big basket, which has a capacity of 200 kg. It reaches 7 m working height.



Safety is ensured during any type of work at height (maintenance, inspection, assembly, etc ...)



The emovable control allows the platform to be raised from the ground.

SOME ACCESSORIES AND CUSTOMISATION



AT 10.1: Power Batteries 12V wit Power connection to the Tractor.

➤ **OTHER ACCESSORIES AND COSTUMISATION ON P. 46**



By using stabilizers and positioning the cage 70 cm above ground level, a working height of 7 m can be reached.

ELEVAH 70

PUSH AROUND MACHINE



ELEVAH[®] 70

	Without Stabilizers	With Stabilizers
Max. working height	6 m (With basket in position 2)	7,25 m (With basket in position 2)
Max capacity	200 kg	
Number of people	1	
Use	Internal	
A Closed machine height	1700 mm	
B Minimum platform height	380 mm	
C Height from ground to walk-on floor	970 mm	
D Maximum platform height	4000 mm	5250 mm*
E Base overall dimensions	1320 mm	1380 mm
F	780 mm	1350 mm
G Cage dimensions	780 mm	
H	850 mm	
I Max. distance from the wall	0 mm	40 mm
J	0 mm	300 mm
K Fixed picking tray dimensions	760 mm	
L	440 mm	
Fixed picking tray capacity	20 kg	
Machine weight with outriggers, 24V power supply	430 kg	
Machine weight with stabilisers (power supply 220V 50/60Hz)	400 kg	
24V power supply 2 Pb Acid batteries 12V	105 Ah	
24V power supply - Battery charger	110V - 220V	
Swivel wheels dimensions (fixed)	Ø 200 x 50 mm	
Swivel wheels dimensions	Ø 150 x 45 mm	
Max. speed (rising)	0,2 m/s	
Max. speed (descending)	0,15 m/s	
L Maximum pressure for wheel at full load**	2,0 kN	
L Maximum pressure for stabilizer at full load**	2,2 kN	
Work cycles (with fresh batteries)***	200	

* Max H. reached with cage at height -C-

** Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

*** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.

  Compliant with **EN280** rule.
Approved for indoor use or outdoor use in the absence of wind.

